



MAXWELL™
RANGE OF PUMPS
An ISO 9001 : 2008 Company





An ISO 9001 : 2008 Company



V5 Mixed Flow

Approximate performance chart of 125 mm (V-5) Mix Flow Submersible Pump Set,
At 2880 RPM, 415 Voltage Three Phase AC Supply 50 Hz Cycle

Suitable For 125 mm & above dia. Borewell

Maximum outside dia of pumpsets : 123 mm

Outlet : 75 mm				Head in Meter	DISCHARGE IN L.P.M.									
MODEL	H.P.	K.W.	STAGE		160	240	290	340	380	430	470	500	540	
M55 - 10	4.00	3.00	4		36	34	32	30	28	26	24	22	20	
M55 - 10	5.00	3.70	5		45	43	40	38	35	33	30	27	25	
M55 - 10	6.00	4.50	6		54	51	48	45	42	39	36	33	30	
M55 - 10	7.50	5.50	8		72	68	64	60	56	52	48	44	40	
M55 - 10	10.00	7.50	10		90	85	80	75	70	65	60	55	50	

Suitable For 125 mm & above dia. Borewell

Maximum outside dia of pumpsets : 125mm

Outlet : 75 mm				Head in Meter	DISCHARGE IN L.P.M.									
MODEL	H.P.	K.W.	STAGE		240	320	380	430	480	540	570	610	660	
M55 - 12	4.00	3.00	3		27	26	24	22	21	19	18	16	15	
M55 - 12	5.00	3.70	4		36	34	32	30	28	26	24	22	20	
M55 - 12	6.00	4.50	5		45	43	40	38	35	33	30	27	25	
M55 - 12	7.50	5.50	6		54	51	48	45	42	39	36	33	30	
M55 - 12	10.00	7.50	8		72	68	64	60	56	52	48	44	40	
M55 - 12	12.50	9.30	10	90	85	80	75	70	65	60	55	50		

Suitable For 125 mm & above dia. Borewell

Maximum outside dia of pumpsets : 125mm

Outlet : 75 mm				Head in Meter	DISCHARGE IN L.P.M.									
MODEL	H.P.	K.W.	STAGE		200	325	450	510	560	650	700	750	800	
M55 - 17	5	3.7	3		27	26	24	22	21	19	18	16	15	
M55 - 17	6	4.5	4		36	34	32	30	28	26	24	22	20	
M55 - 17	7.5	5.5	5		45	43	40	38	35	33	30	27	25	
M55 - 17	10	7.5	6		54	51	48	45	42	39	36	33	30	
M55 - 17	12.5	9.3	8		72	68	64	60	56	52	48	44	40	



RANGE OF PUMPS

An ISO 9001 : 2008 Company



MANUFACTURED BY :

MAXWELL ENGINEERS

PlotNo. B/704, Naroda G.I.D.C.,
Phase-4, Nr. Sharma Hyundai, Gayatri Temple Road,
Naroda, Ahmedabad, Gujarat - 382330
Mobile No: +91-9375088101,
Email-Id: info@maxwellpumps.com

Delears :

