



MAXWELL™
RANGE OF PUMPS
An ISO 9001 : 2008 Company





An ISO 9001 : 2008 Company



V3

Approximate performance chart of 75 mm (V-3) Water Filled Submersible Pump Set, At 2880 RPM, 200-240 Volts Single Phase, AC Supply 50 Hz Cycle

HIGH DISCHARGE SERIES

Suitable For 75 mm & above dia. Borewell

Maximum outside dia of pumpsets : 73 mm

MODEL	H.P.	K.W.	STAGE	Deli. Size mm	Head in Meter	DISCHARGE IN L.P.M.						
						29	48	57	69	82	86	94
MG - 73	0.50	0.37	5	25	15	13	11	10	9	8	6	
MG - 73	0.50	0.37	8	25	24	20	18	16	14	13	10	
MG - 73	0.75	0.55	9	25	27	23	20	18	16	14	11	
MG - 73	1.00	0.75	10	25	30	25	22	20	18	16	13	
MG - 73	1.00	0.75	12	38	36	30	26	24	21	19	15	
MG - 73	1.00	0.75	16	38	48	40	35	32	28	26	20	
MG - 73	1.25	0.93	20	38	60	50	44	40	35	32	25	

ULTRA HEAD SERIES

Suitable For 90mm & above dia. Borewell

Maximum outside dia of pumpsets : 82mm

MODEL	H.P.	K.W.	STAGE	Deli. Size mm	Head in Meter	DISCHARGE IN L.P.M.						
						15	21	26	30	35	42	47
MGH - 82	0.50	0.37	8	25	38	35	32	29	25	21	16	
MGH - 82	0.75	0.55	12	25	57	52	48	43	37	31	24	
MGH - 82	1.00	0.75	16	32	72	66	62	56	48	40	32	
MGH - 82	1.25	0.93	23	32	104	94	89	81	69	58	46	

CAPACITOR DATA FOR PANELS (VOLTAGE RANGE 160 to 230)

H.P.	STARTING CAPACITOR		RUNNING CAPACITOR	
0.50	80	100	36	--
0.75	150	200	36	15
1.00	150	200	36	25
1.25	150	200	36	36





RANGE OF PUMPS

An ISO 9001 : 2008 Company



MANUFACTURED BY :

MAXWELL ENGINEERS

PlotNo. B/704, Naroda G.I.D.C.,
Phase-4, Nr. Sharma Hyundai, Gayatri Temple Road,
Naroda, Ahmedabad, Gujarat - 382330
Mobile No: +91-9375088101,
Email-Id: info@maxwellpumps.com

Delears :

